

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35003233630000

Completion Report

Spud Date: March 14, 2019

OTC Prod. Unit No.: 003-225467-0-0000

Drilling Finished Date: March 29, 2019

1st Prod Date: April 06, 2019

Completion Date: April 05, 2019

Drill Type: HORIZONTAL HOLE

Well Name: WAMPLER 23-26-11 3H

Purchaser/Measurer: WILLIAMS

Location: ALFALFA 14 26N 11W
SE SW SE SE
175 FSL 710 FEL of 1/4 SEC
Latitude: 36.725067469 Longitude: -98.344367624
Derrick Elevation: 1186 Ground Elevation: 1168

First Sales Date: 04/06/2019

Operator: BCE-MACH LLC 24174

14201 WIRELESS WAY STE 300
OKLAHOMA CITY, OK 73134-2512

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	708221		693195	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13.375	48	H-40	628		495	SURFACE
INTERMEDIATE	7	26	P-110	5856		220	3261

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	11.6	L-80	4889	0	0	5729	

Total Depth: 10625

Packer	
Depth	Brand & Type
5433	AS1X

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
May 01, 2019	MISSISSIPPIAN	216	39	764	3537	1741	GASLIFT			137

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPIAN

Code: 359MSSP

Class: OIL

Spacing Orders

Order No	Unit Size
621172	640

Perforated Intervals

From	To
5851	10625

Acid Volumes

262 BBLS 15% HCL

Fracture Treatments

36797 BBLS / 658710 LBS

Formation	Top
MISSISSIPPIAN	5442

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OH PACKER/SLEEVE SYSTEM.

Lateral Holes

Sec: 23 TWP: 26N RGE: 11W County: ALFALFA

SW SE SE SE

298 FSL 621 FEL of 1/4 SEC

Depth of Deviation: 4996 Radius of Turn: 545 Direction: 180 Total Length: 4774

Measured Total Depth: 10625 True Vertical Depth: 5554 End Pt. Location From Release, Unit or Property Line: 298

FOR COMMISSION USE ONLY

1143094

Status: Accepted