

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35011241860000

Completion Report

Spud Date: April 10, 2019

OTC Prod. Unit No.: 01122599100000

Drilling Finished Date: April 30, 2019

1st Prod Date: September 05, 2019

Completion Date: September 05, 2019

Drill Type: HORIZONTAL HOLE

Min Gas Allowable: Yes

Well Name: PICKAROON 11_2-15N-10W 2HX

Purchaser/Measurer: ENLINK

Location: BLAINE 11 15N 10W
SW SW SE SW
320 FSL 1540 FWL of 1/4 SEC
Latitude: 35.78410524 Longitude: -98.23718164
Derrick Elevation: 1334 Ground Elevation: 1311

First Sales Date: 09/05/2019

Operator: DEVON ENERGY PRODUCTION CO LP 20751

333 W SHERIDAN AVE
OKLAHOMA CITY, OK 73102-5015

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
705837	

Increased Density	
Order No	
703910	
693415	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
CONDUCTOR	20	106.5	K-55	65			0
SURFACE	13 3/8	54.5	K-55	1516		1205	SURFACE
INTERMEDIATE	8 5/8	32	P-110EC	9068		355	6441
PRODUCTION	5 1/2	20	P-110EC	20406		1660	4475

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 20418

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
20203	ALUMINUM

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Oct 06, 2019	MISSISSIPPI SOLID/ MISSISSIPPIAN	664	49	2459	3703	754	FLOWING	1240	26/64	1223

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPI SOLID

Code: 351MSSSD

Class: OIL

Spacing Orders

Order No	Unit Size
176175	640
706067	MULTIUNIT

Perforated Intervals

From	To
10537	15293

Acid Volumes

NONE

Fracture Treatments

307828 BBLs OF TOTAL FLUID
26985345 # OF TOTAL PROPPANT

Formation Name: MISSISSIPPIAN

Code: 359MSSP

Class: OIL

Spacing Orders

Order No	Unit Size
589546	640
706067	MULTIUNIT

Perforated Intervals

From	To
15293	20188

Acid Volumes

There are no Acid Volume records to display.

Fracture Treatments

FRAC'D WITH MISSISSIPPI SOLID

Formation Name: MISSISSIPPI SOLID/
MISSISSIPPIAN

Code:

Class: OIL

Formation	Top
MISSISSIPPIAN	9350
MISSISSIPPI SOLID	10165

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

IRREGULAR SECTION

Lateral Holes

Sec: 2 TWP: 15N RGE: 10W County: BLAINE

NE NW NW NW

51 FNL 368 FWL of 1/4 SEC

Depth of Deviation: 9809 Radius of Turn: 543 Direction: 354 Total Length: 9755

Measured Total Depth: 20418 True Vertical Depth: 10047 End Pt. Location From Release, Unit or Property Line: 51

FOR COMMISSION USE ONLY

1143999

Status: Accepted