

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35011241870000

Completion Report

Spud Date: May 01, 2019

OTC Prod. Unit No.: 01122599200000

Drilling Finished Date: May 16, 2019

1st Prod Date: September 05, 2019

Completion Date: September 05, 2019

Drill Type: HORIZONTAL HOLE

Min Gas Allowable: Yes

Well Name: PICKAROON 11_2-15N-10W 3HX

Purchaser/Measurer: ENLINK

Location: BLAINE 11 15N 10W
SW SW SE SW
320 FSL 1570 FWL of 1/4 SEC
Latitude: 35.78410471 Longitude: -98.23708061
Derrick Elevation: 1334 Ground Elevation: 1311

First Sales Date: 09/05/2019

Operator: DEVON ENERGY PRODUCTION CO LP 20751

333 W SHERIDAN AVE
OKLAHOMA CITY, OK 73102-5015

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
705879	

Increased Density	
Order No	
703910	
693415	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
CONDUCTOR	20	106.5	K-55	65			0
SURFACE	13 3/8	54.5	J-55	1488		1205	SURFACE
INTERMEDIATE	8 5/8	32	P-110EC	8978		430	5726
PRODUCTION	5 1/2	20	P-110EC	20150		1645	4697

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 20160

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
19945	ALUMINUM

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Oct 15, 2019	MISSISSIPPI SOLID/ MISSISSIPPIAN	1063	49	2912	2739	141	FLOWING	1260	26/64	1228

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPI SOLID

Code: 351MSSSD

Class: OIL

Spacing Orders

Order No	Unit Size
176175	640
706068	MULTIUNIT

Perforated Intervals

From	To
10419	15023

Acid Volumes

NONE

Fracture Treatments

308689 BBLs OF TOTAL FLUID
27027721 # OF TOTAL PROPPANT

Formation Name: MISSISSIPPIAN

Code: 359MSSP

Class: OIL

Spacing Orders

Order No	Unit Size
589546	640
706068	MULTIUNIT

Perforated Intervals

From	To
15023	19930

Acid Volumes

There are no Acid Volume records to display.

Fracture Treatments

FRAC'D WITH MISSISSIPPI SOLID

Formation Name: MISSISSIPPI SOLID/
MISSISSIPPIAN

Code:

Class: OIL

Formation	Top
MISSISSIPPIAN	9320
MISSISSIPPI SOLID	10130

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

IRREGULAR SECTION

Lateral Holes

Sec: 2 TWP: 15N RGE: 10W County: BLAINE

NW NE NW NE

50 FNL 1788 FEL of 1/4 SEC

Depth of Deviation: 9810 Radius of Turn: 603 Direction: 356 Total Length: 9403

Measured Total Depth: 20160 True Vertical Depth: 10068 End Pt. Location From Release, Unit or Property Line: 50

FOR COMMISSION USE ONLY

1144002

Status: Accepted