

Oklahoma Corporation Commission
 Oil & Gas Conservation Division
 Post Office Box 52000
 Oklahoma City, Oklahoma 73152-2000
 Rule 165: 10-3-25

Form 1002A

API No.: 35011241810000

Completion Report

Spud Date: April 04, 2019

OTC Prod. Unit No.: 011-225801-0-0000

Drilling Finished Date: May 07, 2019

1st Prod Date: June 19, 2019

Completion Date: June 15, 2019

Drill Type: HORIZONTAL HOLE

Well Name: NITZEL 4-18 1412MH

Purchaser/Measurer: REDCLIFF

Location: BLAINE 7 14N 12W
 SW SE SW SW
 250 FSL 960 FWL of 1/4 SEC
 Latitude: 35.696855 Longitude: -98.522076
 Derrick Elevation: 1505 Ground Elevation: 1475

First Sales Date: 06/19/2019

Operator: TRIUMPH ENERGY PARTNERS LLC 23826

8908 S YALE AVE STE 250
 TULSA, OK 74137-3557

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
711260	

Increased Density	
Order No	
690768	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13.375	54.5	J55	1535		1230	SURFACE
INTERMEDIATE	9.625	40	P110	10660		715	SURFACE
PRODUCTION	5.5	20	P110	17928		1765	10287

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 17953

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Jul 12, 2019	MISS'AN LM	203	55.8	14700	72414	1350	FLOW	4228	30/64	0.01

Completion and Test Data by Producing Formation

Formation Name: MISS'AN LM

Code: 359MPLM

Class: GAS

Spacing Orders

Order No	Unit Size
137604	640

Perforated Intervals

From	To
17821	12602

Acid Volumes

480 BBL 15% NEFE HCL

Fracture Treatments

203,870 BBL FLUID AND 11,358,140# SAND

Formation	Top
TONKAWA	7828
COTTAGE GROVE	8345
VERDIGRIS	9881
INOLA	10585
ATOKA	10667
13 FINGERS	10758
MORROW	10845
CHESTER SHALE	11347
CHESTER DENSE	11458
MERAMEC	12487

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

There are no Other Remarks.

Lateral Holes

Sec: 18 TWP: 14N RGE: 12W County: BLAINE

SW SE SW SW

73 FSL 931 FWL of 1/4 SEC

Depth of Deviation: 12156 Radius of Turn: 675 Direction: 182 Total Length: 4737

Measured Total Depth: 17953 True Vertical Depth: 12831 End Pt. Location From Release, Unit or Property Line: 73

FOR COMMISSION USE ONLY

1143229

Status: Accepted