

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35151245870000

Completion Report

Spud Date: January 01, 2020

OTC Prod. Unit No.: 151-226510-0-0000

Drilling Finished Date: January 17, 2020

1st Prod Date: January 24, 2020

Completion Date: January 24, 2020

Drill Type: HORIZONTAL HOLE

Well Name: VERLIN 17-27-16 2H

Purchaser/Measurer: SEMGAS

Location: WOODS 17 27N 16W
NE NW NW NW
277 FNL 335 FWL of 1/4 SEC
Latitude: 36.82604048 Longitude: -98.95161713
Derrick Elevation: 1832 Ground Elevation: 1814

First Sales Date: 1/24/2020

Operator: BCE-MACH LLC 24174

14201 WIRELESS WAY STE 300
OKLAHOMA CITY, OK 73134-2512

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	712670		704665	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13.375	48	J-55	782		630	SURFACE
INTERMEDIATE	7	26	P-110	6171		220	3420

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	11.6	P-110	4698	0	0	6060	10758

Total Depth: 11040

Packer	
Depth	Brand & Type
5816	AS1X

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Feb 12, 2020	MISSISSIPPIAN	183		2137	11677	1466	GASLIFT		128	128

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPIAN

Code: 359MSSP

Class: OIL

Spacing Orders

Order No	Unit Size
595923	640

Perforated Intervals

From	To
6171	11040

Acid Volumes

262 BBLS 15% HCL

Fracture Treatments

37228 BBLS / 0 LBS SAND

Formation	Top
------------------	------------

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OH PACKER/SLEEVE SYSTEM.

Lateral Holes

Sec: 17 TWP: 27N RGE: 16W County: WOODS

SE SW SW SW

170 FSL 650 FWL of 1/4 SEC

Depth of Deviation: 5290 Radius of Turn: 808 Direction: 179 Total Length: 4481

Measured Total Depth: 11040 True Vertical Depth: 5776 End Pt. Location From Release, Unit or Property Line: 170

FOR COMMISSION USE ONLY

1144825

Status: Accepted